

# 90 Degree Pencil Probes with Delrin Tip (Drunk Probes)



- These Probes Significantly Reduce Unwanted Signals Caused by Probe Tilt
- Select either Shielded or Unshielded.
- Standard Probe Length is 6".
- Select Fischer Triaxial or Microdot connector
- Probes with Fischer Triaxial Connectors have Integral Reference Coils

Part #	CONNECTOR TYPE				FREQUENCY
	Unshielded Microdot	Ferrite Shielded Microdot	Unshielded Triax	Ferrite Shielded Triax	50 kHz to 500 kHz
<b>Delrin Tip Tapered 3/16" to 1/16" with 30° Bend in Shaft 2.0" From Tip</b>					
VM229UP-1/4 x 6	✓				✓
VM2529UP-1/4 x 6			✓		✓
<b>Delrin Tip Rounded 1/4" with 30° Bend in Shaft 1.0" From Tip</b>					
VM615URD-1/4 x 6	✓				✓
VM615FRD-1/4 x 6		✓			✓
VM6515URD-1/4 x 6			✓		✓
VM6515FRD-1/4 x 6				✓	✓
<b>Delrin Tip Tapered .187" to .063" with Flexible Copper Shaft</b>					
VMFXP6-.XXX	✓				✓
VMFX5P6-.XXX			✓		✓

